## CE693: Adv. Computer Networking

## L-09 Wireless in the Real World Fall 1390

Acknowledgments: Lecture slides are from the graduate level Computer Networks course thought by Srinivasan Seshan at CMU. When slides are obtained from other sources, a a reference will be noted on the bottom of that slide. A full list of references is provided on the last slide.



- Real world deployment patterns
- Mesh networks and deployments
- Assigned reading
  - Architecture and Evaluation of an Unplanned 802.11b Mesh Network
  - White Space Networking with Wi-Fi like
    Connectivity

# Wireless Challenges



- Force us to rethink many assumptions
- Need to share airwaves rather than wire
  - Don't know what hosts are involved
  - Host may not be using same link technology
- Mobility
- Other characteristics of wireless
  - Noisy  $\rightarrow$  lots of losses
  - Slow
  - Interaction of multiple transmitters at receiver
    - Collisions, capture, interference
  - Multipath interference





### • 802.11

- Deployment patterns
- Reaction to interference
- Interference mitigation
- Mesh networks
  - Architecture
  - Measurements
- White space networks

# Characterizing Current Deployments



- Datasets
- Place Lab: 28,000 APs
  - MAC, ESSID, GPS
  - Selected US cities
  - www.placelab.org
- Wifimaps: 300,000 APs
  - MAC, ESSID, Channel, GPS (derived)
  - wifimaps.com
- Pittsburgh Wardrive: 667 APs
  - MAC, ESSID, Channel, Supported Rates, GPS





### (Placelab: 28000 APs, MAC, ESSID, GPS)

		degree
Portland	8683	54
San Diego	7934	76
San Francisco	3037	85
Boston	2551	39

#APs Max.









## **Unmanaged Devices**



WifiMaps.com (300,000 APs, MAC, ESSID, Channel)

### Channel %age

6	51	
11	21	
1	14	
10	4	

- Most users don't change default channel
- Channel selection must be automated



- Anecdotal evidence of problems, but how severe?
- Characterize how 802.11 operates under interference in practice



# What do we expect?

- Throughput to decrease linearly with interference
- There to be lots of options for 802.11 devices to tolerate interference
  - Bit-rate adaptation
  - Power control
  - FEC
  - Packet size variation
  - Spread-spectrum processing
  - Transmission and reception diversity







- How damaging can a low-power and/or narrow-band interferer be?
- How can today's hardware tolerate interference well?
  - What 802.11 options work well, and why?

## What we see

- Effects of interference more severe in practice
- Caused by hardware limitations of commodity cards, which theory doesn't model



Interferer power (log-scale)



# **Timing Recovery Interference**

- Interferer sends continuous SYNC pattern
- Interferes with packet acquisition (PHY reception errors)



# **Interference Management**



- Interference will get worse
  - Density/device diversity is increasing
  - Unlicensed spectrum is not keeping up
- Spectrum management
  - "Channel hopping" 802.11 effective at mitigating some performance problems [Sigcomm07]
  - Coordinated spectrum use based on RF sensor network
- Transmission power control
  - Enable spatial reuse of spectrum by controlling transmit power
  - Must also adapt carrier sense behavior to take advantage





- 802.11
  - Deployment patterns
  - Reaction to interference
  - Interference mitigation
- Mesh networks
  - Architecture
  - Measurements
- White space networks

## Roofnet



- Share a few wired Internet connections
- Goals
  - Operate without extensive planning or central management
  - Provide wide coverage and acceptable performance
- Design decisions
  - Unconstrained node placement
  - Omni-directional antennas
  - Multi-hop routing
  - Optimization of routing for throughput in a slowly changing network

# **Roofnet Design**



- Deployment
  - Over an area of about four square kilometers in Cambridge, Massachusetts
  - Most nodes are located in buildings
    - 3~4 story apartment buildings
    - 8 nodes are in taller buildings
  - Each Rooftnet node is hosted by a volunteer user
- Hardware
  - PC, omni-directional antenna, hard drive ...
  - 802.11b card
    - RTS/CTS disabled
    - Share the same 802.11b channel
    - Non-standard "pseudo-IBSS" mode
      - Similar to standard 802.11b IBSS (ad hoc)
      - Omit beacon and BSSID (network ID)

## **Roofnet Node Map**





# **Typical Rooftop View**





# A Roofnet Self-Installation Kit



Antenna (\$65) 8dBi, 20 degree vertical

**Computer** (\$340) 533 MHz PC, hard disk, CDROM

802.11b card (\$155) Engenius Prism 2.5, 200mW



50 ft. Cable (\$40) Low loss (3dB/ 100ft) **Miscellaneous** (\$75) Chimney Mount, Lightning Arrestor, Software ("free") Our networking software based on Click **Total: \$685** 

Takes a user about 45 minutes to install on a flat roof

# Software and Auto-Configuration



- Linux, routing software, DHCP server, web server ...
- Automatically solve a number of problems
  - Allocating addresses
  - Finding a gateway between Roofnet and the Internet
  - Choosing a good multi-hop route to that gateway
- Addressing
  - Roofnet carries IP packets inside its own header format and routing protocol
  - Assign addresses automatically
  - Only meaningful inside Roofnet, not globally routable
  - The address of Roofnet nodes
    - Low 24 bits are the low 24 bits of the node's Ethernet address
    - High 8 bits are an unused class-A IP address block
  - The address of hosts
    - Allocate 192.168.1.x via DHCP and use NAT between the Ethernet and Roofnet

Software and Auto-Configuration



- Gateway and Internet Access
  - A small fraction of Roofnet users will share their wired Internet access links
  - Nodes which can reach the Internet
    - Advertise itself to Roofnet as an Internet gateway
    - Acts as a NAT for connection from Roofnet to the Internet
  - Other nodes
    - Select the gateway which has the best route metric
  - Roofnet currently has four Internet gateways

### Roofnet





## Lossy Links are Common





# Delivery Probabilities are Uniformly Distributed





# Delivery vs. SNR









May interfere but not impact SNR measurement





- Top is typical of bursty interference, bottom is not
- Most links are like the bottom



# Is it Multipath Interference?





• Simulate with channel emulator



# **A Plausible Explanation**



- Multi-path can produce intermediate loss rates
- Appropriate multi-path delay is possible due to long-links





- Lack of a link abstraction!
  - Links aren't on or off... sometimes in-between
- Protocols must take advantage of these intermediate quality links to perform well
- How unique is this to Roofnet?
  - Cards designed for indoor environments used outdoors

# **ETX** measurement results



- Delivery is probabilistic
  - A 1/r^2 model wouldn't really predict this!
  - Sharp cutoff (by spec) of "good" vs "no" reception. Intermediate loss range band is just a few dB wide!
- Why?
  - Biggest factor: Multi-path interference
    - 802.11 receivers can suppress reflections < 250ns
    - Outdoor reflections delay often > 1 \mu sec
    - Delay offsets == symbol time look like valid symbols (large interferece)
    - Offsets != symbol time look like random noise
    - Small changes in delay == big changes in loss rate



- Most early protocols: Hop Count
  - Link-layer retransmission can mask some loss
  - But: a 50% loss rate means your link is only 50% as fast!
- Threshold?
  - Can sacrifice connectivity. 🛞
  - Isn't a 90% path better than an 80% path?
- Real life goal: Find highest throughput paths



- Cut-off threshold
  - Disconnected network
- Product of link delivery ratio along path
  - Does not account for inter-hop interference
- Bottleneck link (highest-loss-ratio link)
  - Same as above
- End-to-end delay
  - Depends on interface queue lengths

# **ETX Metric Design Goals**



- Find high throughput paths
- Account for lossy links
- Account for asymmetric links
- Account for inter-link interference
- Independent of network load (don't incorporate congestion)

## Forwarding Packets is Expensive

- Throughput of 802.11b =~ 11Mbits/s
  - In reality, you can get about 5.
- What is throughput of a chain?
  - $A \rightarrow B \rightarrow C$  ?
  - $A \rightarrow B \rightarrow C \rightarrow D$  ?
  - Assume minimum power for radios.
- Routing metric should take this into account! Affects throughput

## ETX



- Measure each link's delivery probability with broadcast probes (& measure reverse)
- P(delivery) = ( d<sub>f</sub> \* d<sub>r</sub> ) (ACK must be delivered too...)
- Link ETX = 1 / P(delivery)
- Route ETX =  $\Sigma$  link ETX
  - Assumes all hops interfere not true, but seems to work okay so far

# **ETX: Sanity Checks**



- ETX of perfect 1-hop path: 1
- ETX of 50% delivery 1-hop path: 2
- ETX of perfect 3-hop path: 3
- (So, e.g., a 50% loss path is better than a perfect 3-hop path! A threshold would probably fail here...)



- What if links @ different rates?
- ETT expected *transmission time* 
  - ETX / Link rate = 1 / ( P(delivery) \* Rate)
- What is best rate for link?
  - The one that minimizes ETT for the link!
  - SampleRate is a technique to adaptively figure this out.

# Discussion



- Value of implementation & measurement
  - Simulators did not "do" multipath
    - Routing protocols dealt with the simulation environment just fine
    - Real world behaved differently and really broke a lot of the proposed protocols that worked so well in simulation!
- Rehash: Wireless differs from wired...
- Metrics: Optimize what matters; hop count often a very bad proxy in wireless
- What we didn't look at: routing protocol overhead
  - One cool area: Geographic routing





- 802.11
  - Deployment patterns
  - Reaction to interference
  - Interference mitigation
- Mesh networks
  - Architecture
  - Measurements
- White space networks





# What are White Spaces?



# The Promise of White Spaces



# White Spaces Spectrum Availability



**# Contiguous Channels** 

Each TV Channel is 6 MH Spectrum is Fragmented nnels for more bandwidth

# White Spaces Spectrum Availability



# White Spaces Spectrum Availability



Incumbents appear/disappear over time

⇒ Must reconfigure after disconnection





#### Fixed Width Channels $\Rightarrow$ Optimize *which* channel to use

## Spectrum Assignment in WhiteFi



### **Spectrum Assignment Problem** Goal **Maximize Throughput** Include **Spectrum at clients Center Channel** Assign R Width Optimize for *both*, **center channel** and **width** Fragmentation $\Rightarrow$ BS must use channel *iff* free at client **Spatial Variation**













Intuition



Intuition Use widest possible channel But Limited by most busy channel 1 2 3 4

- Carrier Sense Across All Channels
- All channels must be free • $\rho_{BS}(2 \text{ and } 3 \text{ are free}) = \rho_{BS}(2 \text{ is free}) \times \rho_{BS}(3 \text{ is free})$

Tradeoff between wider channel widths and opportunity to transmit on each channel



### **Discovery Time =** $O(B \times W)$

Fragmentation  $\Rightarrow$  Try different center channel and widths channels used by the BS?

